


600, 700, AND 900-SERIES ENCLOSED TRACK TRACTOR DRIVE

Operator's Instruction Manual





WARNING

SPANCO CONDITIONS OF USE AND WARNING STATEMENT

1. Read, understand, and follow the manual, assembly drawings, and warnings provided with your system **before** beginning installation. Follow all instructions carefully.
2. This manual must be used in conjunction with manual 103-0010 (Ceiling-Mounted Monorail Manual) or manual 103-0011 (Freestanding Workstation Bridge Crane Manual).
3. This manual, and any other instructions, must be provided to the users of this equipment. The user must understand the equipment's proper use and limitations.
4. For this tractor drive, this crane is engineered to accommodate a standard hoist and a standard hoist weight. The standard hoist weight is calculated at 15 percent of the crane's rated capacity. Please inform Spanco, Inc. if hoist weight exceeds 15 percent of the crane's rated capacity, or if the lifting speed exceeds 50 F.P.M.
5. *Soft starts* and instantaneous *contactor* controls aren't supplied on Spanco systems and are not recommended or acceptable for use on Spanco systems.
6. Each component and system must be employed and maintained according to all OSHA, ANSI, CMAA, and MMA standards.
7. Per OSHA, ANSI, CMAA, and MMA requirements, designate a competent person who can fulfill obligations of all regulations.
8. The rated capacity is displayed on a label on the system. Exceeding the capacities displayed on this label can result in serious injury or death.
9. Never use this system as fall protection or for lifting, hoisting, or carrying personnel.
10. Although Spanco, Inc. may provide components that are intended for service in a specific environment, it is the customer's responsibility to confirm that the provided Spanco system and components will work in and are acceptable for their specific application and environment.
11. **Before each use**, inspect the system for bent, broken, cracked, or missing components, oil leaks, corrosion, properly secured hardware, and any unusual wear or sounds. If any damage is discovered, immediately remove the crane from service until all issues have been resolved and inspected by a qualified person.
12. Thoroughly inspect the system **annually** per OSHA law.
13. There should never be any type of loading past the end stops for any reason.
14. When connecting track sections on runway systems, track splice and truss splice plates are required. For trussed track, splice joint centers must be within maximum 48 inches of the hanger support centers unless otherwise specified. For plain track, splice track centers must be within maximum 18 inches of the hanger support centers unless otherwise specified.
15. Systems with flush clamp hangers do not require sway bracing. However, all systems mounted to the ceiling must be laterally and longitudinally braced with bracing provided by others.
16. For foundation-mounted systems, bracing is not required for non-seismic applications. However, if any sway is perceived as undesirable, lateral bracing can be installed to the system by others. To achieve desired rigidity for a specific application, Spanco, Inc. recommends consulting a professional engineer in your area to satisfy all codes and ordinances.
17. Engineering of any attachment points must be done by others.
18. Component appearances and dimensions shown are approximate and subject to change without notice. All brochure dimensions are developed using standard components for the spans and capacities. Substitution of optional trolleys or other components will affect certain dimensions.
19. Spanco cranes are designed to lift loads straight up and down. Never load the track at an angle.
20. Never deviate from the above unless you have written permission and authorization from Spanco, Inc.



WARNING

ALL FIELD INSTALLATIONS AND CONNECTIONS MUST BE PERFORMED BY A CERTIFIED ELECTRICIAN
TROUBLESHOOTING MUST BE PERFORMED BY A CERTIFIED CRANE TECHNICIAN

SYSTEM APPLICATIONS

The Spanco System is used for material handling applications. This material handling system is labeled with a maximum rated capacity and is designated for Class C service as defined by the CMAA; follow all limitations as noted on system labels.

STANDARDS AND COMPLIANCE

Please refer to local, state, and federal (OSHA) requirements governing occupational safety for additional information regarding material handling. The Spanco System meets or exceeds the requirements set forth in OSHA 1910.179, ANSI B30.11, and MMA MH27.2 and CMAA 70.

REQUIRED TRAINING

This system is intended to be used by people who are trained in its correct application and use. It is the responsibility of the users and the users' management to assure that they are familiar with OSHA law and these instructions, and that they are trained in the correct use and care of this equipment. Authorized users must also be aware of the operating characteristics, application limits, and the consequences of improper use, which can result in serious injury or death.

Every material handling application must be part of a comprehensive managed lift plan. Each program must include, but is not limited to:

- Hazard analysis
- Operator certification training
- Operator evaluation program
- Hand signal protocols
- Lock-out/Tag-out training

The above list is not a comprehensive list. Specific applications may need to include additional items, such as administrative controls or engineered controls. A Qualified Engineer or OSHA Qualified Person should review the comprehensive managed lift plan to ensure that it is adequate for your specific application. CMAA 79 Crane Operator's Manual must be read and followed in its entirety to help ensure worker safety and to create a comprehensive lift plan within your facility.

TABLE OF CONTENTS

CONDITIONS OF USE AND WARNINGS STATEMENT i-ii

SYSTEM APPLICATIONS ii

STANDARDS AND COMPLIANCE ii

REQUIRED TRAINING ii

INSTALLATION INSTRUCTIONS 2-3

MAINTENANCE 3

COMPONENT DRAWINGS 4-13

ELECTRICAL DRAWINGS 14-25

TROUBLESHOOTING 26-27

REDUCER IPTS, INC. BLUE LINE OPERATING INSTRUCTIONS 27

PRODUCT WARRANTY COVERAGE AND SERVICE POLICY 28

ABOUT SPANCO BACK COVER

ASSEMBLY INSTRUCTIONS

1. Equipment That May Be Needed for Assembly

- a) This manual
- b) The inverter manual
- c) Applicable safety equipment for workers' use during assembly, such as hard hats, safety shoes, etc.
- d) Telescoping fork truck or crane (minimum lifting height: determined by installed system height; minimum capacity: 4,000 pounds)
- e) Man lift/cherry picker (minimum height: determined by installed system height)
- f) Measuring tape
- g) Torque wrench
- h) Lifting straps
- i) Two six-inch by six-inch (or larger) wood blocks
- j) Long carpenter's level or laser level
- k) Wrench/Socket sizes: 3/4 inch, 15/16 inch, and 1-1/8 inch
- l) A spacious, level area for assembly
- m) A way to mark hanger locations, such as a permanent marker

2. Inventory

- a) Open all bundles and confirm that all components are accounted for: see your order specific layout drawing. Note that the quantity of components in an assembly are multiplied by the number of the assemblies.
- b) Check for damage to components that may have occurred during shipping.

INSTALLATION

NOTE: All field adjustments and connections must be performed by a certified industrial electrician.

Carefully remove the end stop(s) from the end of the bridge or runway track. Insert the tractor drive into the end of the track making sure that the end of the tractor drive that connects to the hoist trolley (if bridge tractor drive) or the bridge end trucks (if runway tractor drive) goes in first and is facing the mating end of the hoist trolley or bridge end trucks. After the tractor drive is in the track, reinstall the end stop(s).

At the opposite end of the tractor drive is a spring-loaded trolley. Release the compression on the spring to disengage the drive wheel from the track so that the tractor drive can be moved by hand for connecting with the hoist trolley or the bridge end trucks.

After connecting to the hoist trolley or the bridge end trucks and before engaging the drive wheel with the track via the spring-loaded trolley, electrically connect the tractor drive (via the control panel, if applicable). Make sure that the power is turned off when connecting or disconnecting power leads. After the connections are made, check for correct drive wheel rotation. Correct if necessary. The standard speed is 25/50 F.P.M. The inverter can be adjusted to provide speeds up to 100 F.P.M. Refer to the inverter manual for more information.

After the drive wheel rotation is correct, engage the drive wheel to the track by compressing the spring on the spring-loaded trolley with the nut and locking with the jam nut. For a trolley drive (without load), tighten the nut for the spring just enough so that the tractor can no longer be moved forward or backward by hand inside the track, then tighten as per the below instructions up to a maximum additional 2-1/2 complete revolutions to achieve the correct spring pressure. Generally, this procedure should provide the correct amount of friction to move properly when under load. Also, refer to the **Tractor Drive Adjustment Procedure** below as an alternative procedure.

NOTE: Never exceed more than 2-1/2 complete revolutions of the nuts when compressing the spring or permanent damage to the drive wheel could result.

MAINTENANCE:

Refer to the attachments for maintenance of the gearbox. Slippage of the drive wheel can be corrected by adjusting the compression of the spring on the spring-loaded trolley. Replace the drive wheel when all the adjustment is taken up on the spring-loaded trolley, or if section(s) of the tread are missing or loose.


TRACTOR DRIVE ADJUSTMENT PROCEDURE

- 1) Adjust the double hex nuts under the spring on the guide trolley assembly so that the drive wheel is not in contact with the track.
- 2) Tighten the first nut until the drive wheel contacts the track.
- 3) Give the first nut an additional 1/2 turn and tighten the second nut against it.
- 4) When the tractor drive is ready to test, note the amount of slip that occurs at start-up. The drive wheel can slip for a maximum of approximately 1/2 to one second while the bridge comes to full speed. Excessive slip is not acceptable.
- 5) Adjust the double hex nuts under the spring on the guide trolley assembly again if required to achieve proper engagement.


NOTE: Never exceed more than 2-1/2 complete revolutions of the nuts when compressing the spring or permanent damage to the drive wheel could result.

ITEM NO.	QTY.	PART NO.	DESCRIPTION
1	1	109-0826	WELMENT MAIN FRAME EC TRAC DRIVE 600
2	1	109-0828	PLATE GUE TRLY NO SPRING EC TRAC DRV 600
3	1	109-0829	WELMENT 600 ONE TRILEY EC TRAC DRV
4	1	102-0005	SPRING 88 8/77 X 0.75 DIA X 0.75 FREE LENGTH
5	1	102-0005	SPRING 88 8/77 X 0.75 DIA X 0.75 FREE LENGTH
6	1	102-0005	SPRING 88 8/77 X 0.75 DIA X 0.75 FREE LENGTH
7	1	109-0826	WELMENT MAIN FRAME EC TRAC DRIVE 600
8	1	109-0828	PLATE GUE TRLY NO SPRING EC TRAC DRV 600
9	1	109-0829	WELMENT 600 ONE TRILEY EC TRAC DRV
10	1	102-0005	SPRING 88 8/77 X 0.75 DIA X 0.75 FREE LENGTH
11	1	102-0005	SPRING 88 8/77 X 0.75 DIA X 0.75 FREE LENGTH
12	1	102-0005	SPRING 88 8/77 X 0.75 DIA X 0.75 FREE LENGTH
13	1	109-0826	WELMENT MAIN FRAME EC TRAC DRIVE 600
14	1	109-0828	PLATE GUE TRLY NO SPRING EC TRAC DRV 600
15	1	109-0829	WELMENT 600 ONE TRILEY EC TRAC DRV
16	1	102-0005	SPRING 88 8/77 X 0.75 DIA X 0.75 FREE LENGTH
17	1	102-0005	SPRING 88 8/77 X 0.75 DIA X 0.75 FREE LENGTH
18	1	102-0005	SPRING 88 8/77 X 0.75 DIA X 0.75 FREE LENGTH
19	1	109-0826	WELMENT MAIN FRAME EC TRAC DRIVE 600
20	1	109-0828	PLATE GUE TRLY NO SPRING EC TRAC DRV 600
21	1	109-0829	WELMENT 600 ONE TRILEY EC TRAC DRV
22	1	102-0005	SPRING 88 8/77 X 0.75 DIA X 0.75 FREE LENGTH
23	1	102-0005	SPRING 88 8/77 X 0.75 DIA X 0.75 FREE LENGTH
24	1	102-0005	SPRING 88 8/77 X 0.75 DIA X 0.75 FREE LENGTH
25	1	109-0826	WELMENT MAIN FRAME EC TRAC DRIVE 600
26	1	109-0828	PLATE GUE TRLY NO SPRING EC TRAC DRV 600
27	1	109-0829	WELMENT 600 ONE TRILEY EC TRAC DRV
28	1	102-0005	SPRING 88 8/77 X 0.75 DIA X 0.75 FREE LENGTH
29	1	102-0005	SPRING 88 8/77 X 0.75 DIA X 0.75 FREE LENGTH
30	1	102-0005	SPRING 88 8/77 X 0.75 DIA X 0.75 FREE LENGTH
31	1	109-0826	WELMENT MAIN FRAME EC TRAC DRIVE 600
32	1	109-0828	PLATE GUE TRLY NO SPRING EC TRAC DRV 600
33	1	109-0829	WELMENT 600 ONE TRILEY EC TRAC DRV
34	1	102-0005	SPRING 88 8/77 X 0.75 DIA X 0.75 FREE LENGTH
35	1	102-0005	SPRING 88 8/77 X 0.75 DIA X 0.75 FREE LENGTH


NOTE: THE FOLLOWING COMPONENTS ARE INCLUDED WITH 43-0068 (ALL QTY=1):
 09-0826, 09-0827, 14-0002, 20-0026, & 47-0001-0010 (QTY=3).
 NOTE: 73-010 IS INCLUDED WITH 95-0000-3-ETM-00





SECTION B-B
SCALE 1/2"



SECTION A-A
SCALE 1/2"



NOTE: TRACK AND ENDSTOPS SHOWN AS REFERENCE ONLY




"600" WITH CONTROL PANEL

REV.	DATE	BY	DESCRIPTION
1	09-0826	09-0828	ENCLOSED TRACK
2	09-0829	09-0829	ENCLOSED TRACK
3	09-0829	09-0829	ENCLOSED TRACK
4	09-0829	09-0829	ENCLOSED TRACK
5	09-0829	09-0829	ENCLOSED TRACK
6	09-0829	09-0829	ENCLOSED TRACK
7	09-0829	09-0829	ENCLOSED TRACK
8	09-0829	09-0829	ENCLOSED TRACK
9	09-0829	09-0829	ENCLOSED TRACK
10	09-0829	09-0829	ENCLOSED TRACK
11	09-0829	09-0829	ENCLOSED TRACK
12	09-0829	09-0829	ENCLOSED TRACK
13	09-0829	09-0829	ENCLOSED TRACK
14	09-0829	09-0829	ENCLOSED TRACK
15	09-0829	09-0829	ENCLOSED TRACK
16	09-0829	09-0829	ENCLOSED TRACK
17	09-0829	09-0829	ENCLOSED TRACK
18	09-0829	09-0829	ENCLOSED TRACK
19	09-0829	09-0829	ENCLOSED TRACK
20	09-0829	09-0829	ENCLOSED TRACK
21	09-0829	09-0829	ENCLOSED TRACK
22	09-0829	09-0829	ENCLOSED TRACK
23	09-0829	09-0829	ENCLOSED TRACK
24	09-0829	09-0829	ENCLOSED TRACK
25	09-0829	09-0829	ENCLOSED TRACK
26	09-0829	09-0829	ENCLOSED TRACK
27	09-0829	09-0829	ENCLOSED TRACK
28	09-0829	09-0829	ENCLOSED TRACK
29	09-0829	09-0829	ENCLOSED TRACK
30	09-0829	09-0829	ENCLOSED TRACK
31	09-0829	09-0829	ENCLOSED TRACK
32	09-0829	09-0829	ENCLOSED TRACK
33	09-0829	09-0829	ENCLOSED TRACK
34	09-0829	09-0829	ENCLOSED TRACK
35	09-0829	09-0829	ENCLOSED TRACK


600, 700, AND 900-SERIES ENCLOSED TRACK TRACTOR DRIVE MANUAL

ITEM NO.	QTY.	PART NO.	DESCRIPTION
1	1	109-0836	WELMENT MAIN FRAME EC TRAC DRIVE 600
2	1	109-0838	PLATE GUE TRAY NO SPRING EC TRAC DRV 600
3	1	109-0839	WELMENT 600 ONE TRLEY EC TRAC DRV
4	1	102-0005	SPRING 88 #77 X 0.75 DIA X 0.75 FREE LENGTH
5	1	109-0840	WELMENT 600 ONE TRLEY EC TRAC DRV
6	1	109-0841	WELMENT 600 ONE TRLEY EC TRAC DRV
7	1	109-0842	WELMENT 600 ONE TRLEY EC TRAC DRV
8	1	109-0843	WELMENT 600 ONE TRLEY EC TRAC DRV
9	1	109-0844	WELMENT 600 ONE TRLEY EC TRAC DRV
10	1	109-0845	WELMENT 600 ONE TRLEY EC TRAC DRV
11	1	109-0846	WELMENT 600 ONE TRLEY EC TRAC DRV
12	1	109-0847	WELMENT 600 ONE TRLEY EC TRAC DRV
13	1	109-0848	WELMENT 600 ONE TRLEY EC TRAC DRV
14	1	109-0849	WELMENT 600 ONE TRLEY EC TRAC DRV
15	1	109-0850	WELMENT 600 ONE TRLEY EC TRAC DRV
16	1	109-0851	WELMENT 600 ONE TRLEY EC TRAC DRV
17	1	109-0852	WELMENT 600 ONE TRLEY EC TRAC DRV
18	1	109-0853	WELMENT 600 ONE TRLEY EC TRAC DRV
19	1	109-0854	WELMENT 600 ONE TRLEY EC TRAC DRV
20	1	109-0855	WELMENT 600 ONE TRLEY EC TRAC DRV
21	1	109-0856	WELMENT 600 ONE TRLEY EC TRAC DRV
22	1	109-0857	WELMENT 600 ONE TRLEY EC TRAC DRV
23	1	109-0858	WELMENT 600 ONE TRLEY EC TRAC DRV
24	1	109-0859	WELMENT 600 ONE TRLEY EC TRAC DRV
25	1	109-0860	WELMENT 600 ONE TRLEY EC TRAC DRV
26	1	109-0861	WELMENT 600 ONE TRLEY EC TRAC DRV
27	1	109-0862	WELMENT 600 ONE TRLEY EC TRAC DRV
28	1	109-0863	WELMENT 600 ONE TRLEY EC TRAC DRV
29	1	109-0864	WELMENT 600 ONE TRLEY EC TRAC DRV
30	1	109-0865	WELMENT 600 ONE TRLEY EC TRAC DRV
31	1	109-0866	WELMENT 600 ONE TRLEY EC TRAC DRV
32	1	109-0867	WELMENT 600 ONE TRLEY EC TRAC DRV


NOTE: THE FOLLOWING COMPONENTS ARE INCLUDED WITH 43-0068 (ALL QTY=1)
 09-0826, 09-0827, 14-0002, 20-0026, & 47-0001-0010 (QTY=5)





SECTION B-B
SCALE 1:2



SECTION A-A
SCALE 1:2



NOTE: TRACK AND ENVISTOPES SHOWN AS REFERENCE ONLY




REV.	DATE	DESCRIPTION
1	09-0826	ENCLOSED TRACK
2	09-0827	ENCLOSED TRACK
3	14-0002	ENCLOSED TRACK
4	20-0026	ENCLOSED TRACK
5	47-0001	ENCLOSED TRACK
6	47-0010	ENCLOSED TRACK
7	47-0011	ENCLOSED TRACK
8	47-0012	ENCLOSED TRACK
9	47-0013	ENCLOSED TRACK
10	47-0014	ENCLOSED TRACK
11	47-0015	ENCLOSED TRACK
12	47-0016	ENCLOSED TRACK
13	47-0017	ENCLOSED TRACK
14	47-0018	ENCLOSED TRACK
15	47-0019	ENCLOSED TRACK
16	47-0020	ENCLOSED TRACK
17	47-0021	ENCLOSED TRACK
18	47-0022	ENCLOSED TRACK
19	47-0023	ENCLOSED TRACK
20	47-0024	ENCLOSED TRACK
21	47-0025	ENCLOSED TRACK
22	47-0026	ENCLOSED TRACK
23	47-0027	ENCLOSED TRACK
24	47-0028	ENCLOSED TRACK
25	47-0029	ENCLOSED TRACK
26	47-0030	ENCLOSED TRACK
27	47-0031	ENCLOSED TRACK
28	47-0032	ENCLOSED TRACK
29	47-0033	ENCLOSED TRACK
30	47-0034	ENCLOSED TRACK
31	47-0035	ENCLOSED TRACK
32	47-0036	ENCLOSED TRACK


"600" NO CONTROL PANEL

ITEM NO.	QTY.	PART NO.	DESCRIPTION
1	1	109-0088	WELMONT MAIN FRAME EC TRAC DRIVE/700
2	1	109-0089	PLATE GUE TRILY NO SPRING EC TRAC DRV/700
3	2	109-0705	700 SERIES AXLE
4	1	109-0706	PLASTIC WHEEL ASSEMBLY
5	1	109-0707	SPACER DRIVE SHAFT EC TRAC DRV
6	1	109-0708	SPACER 700 SERIES AXLE
7	1	109-0806	WELMONT 600 GUE TRILY EC TRAC DRV
8	2	109-0807	7/8" ID CAM ROLLER
9	2	109-0808	BULLY HEX HEAD 1/4-20 X 1-3/4 LBS
10	1	109-0809	SPRING 88 M/T X 0.75" DIA X 0.75" FREE LENGTH
11	1	109-0810	WELMONT 600 GUE TRILY EC TRAC DRV
12	2	109-0811	BULLY HEX HEAD 1/4-20 X 1-3/4 LBS
13	1	109-0812	WELMONT 600 GUE TRILY EC TRAC DRV
14	1	109-0813	WELMONT 600 GUE TRILY EC TRAC DRV
15	1	109-0814	WELMONT 600 GUE TRILY EC TRAC DRV
16	1	109-0815	WELMONT 600 GUE TRILY EC TRAC DRV
17	1	109-0816	WELMONT 600 GUE TRILY EC TRAC DRV
18	1	109-0817	WELMONT 600 GUE TRILY EC TRAC DRV
19	1	109-0818	WELMONT 600 GUE TRILY EC TRAC DRV
20	1	109-0819	WELMONT 600 GUE TRILY EC TRAC DRV
21	1	109-0820	WELMONT 600 GUE TRILY EC TRAC DRV
22	1	109-0821	WELMONT 600 GUE TRILY EC TRAC DRV
23	1	109-0822	WELMONT 600 GUE TRILY EC TRAC DRV
24	1	109-0823	WELMONT 600 GUE TRILY EC TRAC DRV
25	1	109-0824	WELMONT 600 GUE TRILY EC TRAC DRV
26	1	109-0825	WELMONT 600 GUE TRILY EC TRAC DRV
27	1	109-0826	WELMONT 600 GUE TRILY EC TRAC DRV
28	1	109-0827	WELMONT 600 GUE TRILY EC TRAC DRV
29	1	109-0828	WELMONT 600 GUE TRILY EC TRAC DRV
30	1	109-0829	WELMONT 600 GUE TRILY EC TRAC DRV
31	1	109-0830	WELMONT 600 GUE TRILY EC TRAC DRV
32	1	109-0831	WELMONT 600 GUE TRILY EC TRAC DRV
33	1	109-0832	WELMONT 600 GUE TRILY EC TRAC DRV
34	1	109-0833	WELMONT 600 GUE TRILY EC TRAC DRV
35	1	109-0834	WELMONT 600 GUE TRILY EC TRAC DRV




NOTE: THE FOLLOWING COMPONENTS ARE INCLUDED WITH 43-0068 (ALL QTY=1)
 09-0826, 09-0827, 14-0062, 20-0026, & 47-0001-0010 (QTY=3).
 NOTE: 73-0100 IS INCLUDED WITH 95-0000-3-ETW-00



SECTION B-B
SCALE 1:2





NOTE: TRACK AND ENDSTOPS SHOWN AS REFERENCE ONLY



REV	DATE	BY	DESCRIPTION
1	09-07-08	SP	ENCLOSED TRACK DRIVE
2	09-07-08	SP	ENCLOSED TRACK DRIVE
3	09-07-08	SP	ENCLOSED TRACK DRIVE
4	09-07-08	SP	ENCLOSED TRACK DRIVE
5	09-07-08	SP	ENCLOSED TRACK DRIVE
6	09-07-08	SP	ENCLOSED TRACK DRIVE
7	09-07-08	SP	ENCLOSED TRACK DRIVE
8	09-07-08	SP	ENCLOSED TRACK DRIVE
9	09-07-08	SP	ENCLOSED TRACK DRIVE
10	09-07-08	SP	ENCLOSED TRACK DRIVE
11	09-07-08	SP	ENCLOSED TRACK DRIVE
12	09-07-08	SP	ENCLOSED TRACK DRIVE
13	09-07-08	SP	ENCLOSED TRACK DRIVE
14	09-07-08	SP	ENCLOSED TRACK DRIVE
15	09-07-08	SP	ENCLOSED TRACK DRIVE
16	09-07-08	SP	ENCLOSED TRACK DRIVE
17	09-07-08	SP	ENCLOSED TRACK DRIVE
18	09-07-08	SP	ENCLOSED TRACK DRIVE
19	09-07-08	SP	ENCLOSED TRACK DRIVE
20	09-07-08	SP	ENCLOSED TRACK DRIVE
21	09-07-08	SP	ENCLOSED TRACK DRIVE
22	09-07-08	SP	ENCLOSED TRACK DRIVE
23	09-07-08	SP	ENCLOSED TRACK DRIVE
24	09-07-08	SP	ENCLOSED TRACK DRIVE
25	09-07-08	SP	ENCLOSED TRACK DRIVE
26	09-07-08	SP	ENCLOSED TRACK DRIVE
27	09-07-08	SP	ENCLOSED TRACK DRIVE
28	09-07-08	SP	ENCLOSED TRACK DRIVE
29	09-07-08	SP	ENCLOSED TRACK DRIVE
30	09-07-08	SP	ENCLOSED TRACK DRIVE
31	09-07-08	SP	ENCLOSED TRACK DRIVE
32	09-07-08	SP	ENCLOSED TRACK DRIVE
33	09-07-08	SP	ENCLOSED TRACK DRIVE
34	09-07-08	SP	ENCLOSED TRACK DRIVE
35	09-07-08	SP	ENCLOSED TRACK DRIVE

"700" WITH CONTROL PANEL

NOTE: THE FOLLOWING COMPONENTS ARE INCLUDED WITH 43-0068 (ALL QTY=1):
09-0826, 09-0827, 14-0002, 20-0026, & 47-0001-00.10 (QTY=3).



700” NO CONTROL PANEL

REV.	DATE	DESC	REVISED DESCRIPTION
1	01/20/2018	UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE TO FACE UNLESS NOTED OTHERWISE.	
2	01/20/2018	1" DIA. HOLE	
3	01/20/2018	1" DIA. HOLE	
4	01/20/2018	1" DIA. HOLE	
5	01/20/2018	1" DIA. HOLE	
6	01/20/2018	1" DIA. HOLE	
7	01/20/2018	1" DIA. HOLE	
8	01/20/2018	1" DIA. HOLE	
9	01/20/2018	1" DIA. HOLE	
10	01/20/2018	1" DIA. HOLE	
11	01/20/2018	1" DIA. HOLE	
12	01/20/2018	1" DIA. HOLE	
13	01/20/2018	1" DIA. HOLE	
14	01/20/2018	1" DIA. HOLE	
15	01/20/2018	1" DIA. HOLE	
16	01/20/2018	1" DIA. HOLE	
17	01/20/2018	1" DIA. HOLE	
18	01/20/2018	1" DIA. HOLE	
19	01/20/2018	1" DIA. HOLE	
20	01/20/2018	1" DIA. HOLE	
21	01/20/2018	1" DIA. HOLE	
22	01/20/2018	1" DIA. HOLE	
23	01/20/2018	1" DIA. HOLE	
24	01/20/2018	1" DIA. HOLE	
25	01/20/2018	1" DIA. HOLE	
26	01/20/2018	1" DIA. HOLE	
27	01/20/2018	1" DIA. HOLE	
28	01/20/2018	1" DIA. HOLE	
29	01/20/2018	1" DIA. HOLE	
30	01/20/2018	1" DIA. HOLE	
31	01/20/2018	1" DIA. HOLE	
32	01/20/2018	1" DIA. HOLE	
33	01/20/2018	1" DIA. HOLE	
34	01/20/2018	1" DIA. HOLE	
35	01/20/2018	1" DIA. HOLE	
36	01/20/2018	1" DIA. HOLE	
37	01/20/2018	1" DIA. HOLE	
38	01/20/2018	1" DIA. HOLE	
39	01/20/2018	1" DIA. HOLE	
40	01/20/2018	1" DIA. HOLE	
41	01/20/2018	1" DIA. HOLE	
42	01/20/2018	1" DIA. HOLE	
43	01/20/2018	1" DIA. HOLE	
44	01/20/2018	1" DIA. HOLE	
45	01/20/2018	1" DIA. HOLE	
46	01/20/2018	1" DIA. HOLE	
47	01/20/2018	1" DIA. HOLE	
48	01/20/2018	1" DIA. HOLE	
49	01/20/2018	1" DIA. HOLE	
50	01/20/2018	1" DIA. HOLE	
51	01/20/2018	1" DIA. HOLE	
52	01/20/2018	1" DIA. HOLE	
53	01/20/2018	1" DIA. HOLE	
54	01/20/2018	1" DIA. HOLE	
55	01/20/2018	1" DIA. HOLE	
56	01/20/2018	1" DIA. HOLE	
57	01/20/2018	1" DIA. HOLE	
58	01/20/2018	1" DIA. HOLE	
59	01/20/2018	1" DIA. HOLE	
60	01/20/2018	1" DIA. HOLE	
61	01/20/2018	1" DIA. HOLE	
62	01/20/2018	1" DIA. HOLE	
63	01/20/2018	1" DIA. HOLE	
64	01/20/2018	1" DIA. HOLE	
65	01/20/2018	1" DIA. HOLE	
66	01/20/2018	1" DIA. HOLE	
67	01/20/2018	1" DIA. HOLE	
68	01/20/2018	1" DIA. HOLE	
69	01/20/2018	1" DIA. HOLE	
70	01/20/2018	1" DIA. HOLE	
71	01/20/2018	1" DIA. HOLE	
72	01/20/2018	1" DIA. HOLE	
73	01/20/2018	1" DIA. HOLE	
74	01/20/2018	1" DIA. HOLE	
75	01/20/2018	1" DIA. HOLE	
76	01/20/2018	1" DIA. HOLE	
77	01/20/2018	1" DIA. HOLE	
78	01/20/2018	1" DIA. HOLE	
79	01/20/2018	1" DIA. HOLE	
80	01/20/2018	1" DIA. HOLE	
81	01/20/2018	1" DIA. HOLE	
82	01/20/2018	1" DIA. HOLE	
83	01/20/2018	1" DIA. HOLE	
84	01/20/2018	1" DIA. HOLE	
85	01/20/2018	1" DIA. HOLE	
86	01/20/2018	1" DIA. HOLE	
87	01/20/2018	1" DIA. HOLE	
88	01/20/2018	1" DIA. HOLE	
89	01/20/2018	1" DIA. HOLE	
90	01/20/2018	1" DIA. HOLE	
91	01/20/2018	1" DIA. HOLE	
92	01/20/2018	1" DIA. HOLE	
93	01/20/2018	1" DIA. HOLE	
94	01/20/2018	1" DIA. HOLE	
95	01/20/2018	1" DIA. HOLE	
96	01/20/2018	1" DIA. HOLE	
97	01/20/2018	1" DIA. HOLE	
98	01/20/2018	1" DIA. HOLE	
99	01/20/2018	1" DIA. HOLE	
100	01/20/2018	1" DIA. HOLE	

ITEM NO.

QTY. REQD.

DESCRIPTION

PART NO.

WT.

MAT'L.

REMARKS

1	2	TOW BAR PLATE	TD600-9	54	A-36	
2	ONE	1/2-13 UNC x 1 3/4" LG. BOLT	10-0213			
3	ONE	1/2-13 UNC LOCK NUT	13-0003			
4	ONE	REPLACEMENT LOAD PIN	9-1451			
5	4	FLAT WASHERS	15-0007			
6	2	COTTER PINS	23-0003			

PIN TYPE 1

PIN TYPE 2

4

4

WHEN INSTALLING TRACTOR DRIVE TOW LINKS, REPLACE EXISTING TROLLEY LOAD PIN (PIN TYPE 1) WITH SUPPLIED LOAD PIN (PIN TYPE 2).

TRACTOR DRIVE

TROLLEY

1

2

3

4

TRACTOR DRIVE

TROLLEY

600" HOIST TROLLEY

1618 REF.

1

2

3

4

ELEVATION

600" HOIST TROLLEY

1618 REF.

1

2

3

4

ELEVATION

8/25/20

1/3/14

2-21-01

2-7-01

12-2-99

REV.

DATE

DESCRIPTION

E	8/25/20	1/3/14	2-21-01	2-7-01	12-2-99	REV.	DATE	DESCRIPTION
D	1/3/14	1/3/14	1/3/14	1/3/14	1/3/14	1/3/14	1/3/14	1/3/14
C	2-21-01	1/3/14	1/3/14	1/3/14	1/3/14	1/3/14	1/3/14	1/3/14
B	2-7-01	1/3/14	1/3/14	1/3/14	1/3/14	1/3/14	1/3/14	1/3/14
A	12-2-99	1/3/14	1/3/14	1/3/14	1/3/14	1/3/14	1/3/14	1/3/14

SPANCO[®]

INC.

MOORETOWN BUSINESS PARK, HEBLOCK ROAD, MOORETOWN, PA, 19363

ENCLOSED - TRACK

TRACTOR DRIVES

600 TRACTOR DRIVE

TROLLEY TOW BAR ASSEMBLY

FIG. NO.

TD600-9

REV.

E

Spanco.com • 1-800-869-2080 • Enclosed Track 600-Series Tractor Drive Manual 8

BILL OF MATERIALS


ITEM NO.	QTY. REQD.	DESCRIPTION	PART NO.	WT.	MATL.	REMARKS
1	ONE	TROLLEY TOW BAR ASSY.	TD700-9	5	A-36	
2	ONE	LEFT TOW BAR PLATE	09-0518-1	2	A-36	
3	ONE	RIGHT TOW BAR PLATE	09-0518-2	2	A-36	
4	ONE	1/2-13 UNC x 1 3/4" LG. BOLT	10-0213			
5	ONE	1/2-13 UNC LOCK NUT	13-0023			
6	ONE	REPLACEMENT LOAD PIN	9-1435			
7	2	WASHER, HARDENED 1 1/8" DIA.	15-0023			
8	2	COTTER PIN 5/32" x 3"	23-0003			

**700" HOIST
TROLLEY**

SPANCO INC.
MORGANTOWN BUSINESS PARK, HEMLOCK ROAD, MORGANTOWN, PA. 15043

**ENCLOSED-TRACK
TRACTOR DRIVES
700 TRACTOR DRIVE
TROLLEY TOW BAR ASSEMBLY**

PART NO. TD700-9C
REV. NO. D
DATE 12/23/13
FABRICATION



ITEM NO.

QTY REQD.

DESCRIPTION

PART NO.

WT.

MAT'L.

REMARKS

1	2	BRIDGE TOW BAR ASS'Y.	TD700-10	4		
2	2	BRIDGE TOW BAR	09-0204	3	A-36	
2	2	1/2-13 UNC x 2" LG. BOLT	10-0003			
3	2	1/2-13 UNC LOCK NUT	13-0003			
4	1	1/2-13 UNC x 5" GR5 LG. BOLT	10-0014			

FOR ALL STANDARD ENDTRUCKS
(UP TO 23' LENGTH BRIDGE)

600-700
STD_ENDTRUCK

ENDTRUCK

1

LONG BOLT
REQUIRED (1/2-13UNC X 5 GR5)
1 SHORT BOLT NOT REQUIRED (1/2-13NC X 2)

USE SHORTER
BOLT (1/2-13NC X 2)

HOLE NOT USED

2

3

4

1

2

3

4

REVISION

DATE

BY

DESCRIPTION

C	06/29/20	MLC	UPDATED TRACTOR DRIVE VIEW REMOVED 3D VIEW
B	12/26/13	LAR	MORE DETAILED INSTRUCTIONS
A	11-5-09	SML	CHANGED ENDTRUCK NO.

SPANCO[®]

INC.

MORGANTOWN BUSINESS PARK, HERRLOCK ROAD, MORGANTOWN, PA. 15043

ENCLOSED-TRACK
TRACTOR DRIVES
TRACTOR DRIVE w/STD. ENDTRUCK
BRIDGE TOW BAR ASSEMBLY

REV. NO.

DATE

BY

DESCRIPTION

1	01/10/10	DAJ	10/24/07
2	01/12/10	DAJ	12/29/07
3	01/12/10	DAJ	12/29/07
4	01/12/10	DAJ	12/29/07

PROJECT NO.

END-TRACTORS

12/26/13

FIG. NO.

10700-10B

10700-10

FIG. NO.

10700-10

10700-10

11 Spanco® Enclosed Track 600-Series Tractor Drive Manual • 1-800-869-2080 • Spanco.com

ITEM NO.

QTY. REQD.

DESCRIPTION

PART NO.

WT.

MAT'L.

REMARKS

1	2	BRIDGE TOW BAR ASST.	TD700-10	4		
2	2	BRIDGE TOW BAR	09-0204	3	A-36	
2	2	1/2-13 UNC x 2" LG. BOLT	10-0003			
3	2	1/2-13 UNC LOCK NUT	13-0003			

ENDTRUCK

USE SHORTER BOLT (1/2-13NC X 2)
LONG BOLT NOT REQUIRED (1/2-13NC X 5 GR5)

HOLE NOT USED

TD700-CP8 (REF.)

SALES IN THE USA

STANDARD TRACTOR DRIVE

1

2

3

FOR ENDTRUCK WITH A
SOLID FLAT CENTER PLATE

FLAT_PLATE
&
HYBRID_ENDTRUCK
&
DOUBLE_GIRDER_TROLLEYS

REV.

DATE

BY

CHKD.

DESCRIPTION

C	06/28/20	NLC		UPDATED TRACTOR DRIVE VIEW REMOVED 3D VIEW
B	12/28/13	LAR		MORE DETAILED INSTRUCTIONS
A	11-5-98	SNL		CHANGED ENDTRUCK NO.

SPANCO[®] INC.

MORGANTOWN BUSINESS PARK, HEBLOCK ROAD, MORGANTOWN, PA 15043

ENCLOSED-TRACK
TRACTOR DRIVES
TRACTOR DRIVE W/STD. ENDTRUCK
BRIDGE TOW BAR ASSEMBLY

PROJECT NO. TD700-108-3

DATE 12/26/13

LAYOUT

REV. NO. C

1

2

3

Spanco.com • 1-800-869-2080 • Enclosed Track 600-Series Tractor Drive Manual 12

BILL OF MATERIALS

ITEM NO.	QTY.	REC'D.	DESCRIPTION	PART NO.
1	2		BRIDGE TOW BAR ASSY.	TD700-12
2	2		BRIDGE TOW BAR	09-1392
3	2		1/2-13 UNC x 2" L.G. BOLT	10-0203
4	ONE		1/2-13 UNC LOCK NUT	13-0003
5	ONE		TOW BAR MOUNTING	9-1175
6	ONE		1/2-13 x 1" HEX BOLT	10-0201
			1/2" LOCK WASHER	14-0003

600-700-900
 AND DOUBLE GIRDER
 EXTENDED END TRUCK

NOTE:
 THIS TOW BAR ASSEMBLY MAY BE USED
 IN PLACE OF TD700-11.

ELEVATION
 SCALE: 1 1/2" = 1'-0"

SPANCO[®] INC.
 MORGANTOWN BUSINESS PARK, HERRIDGE ROAD, MORGANTOWN, PA. 15043

DATE: 04/26/20
 DRAWN: DJL
 CHECKED: DLE
 APPROVED: NLS


PROJECT: ENCL-TRACTORS
 DATE: 12/26/13

ENCLOSED-TRACTOR DRIVES
 TRACTOR DRIVE w/EXT. END TRUCK
 BRIDGE TOW BAR ASSEMBLY

REV: 1
 PART NO.: TD700-12-A
 DATE: 12/26/13
 FABRICATION

SELECT MOTOR (NON-WASHDOWN)		
MOTOR	PART No.	SET INVERTER / U22
1/3 HP	48-0001	.65 AMP

SELECT MOTOR (WASHDOWN)		
MOTOR	PART No.	SET INVERTER / U22
1/3 HP	48-0012SS	.65 AMP



BILL OF MATERIALS						
ITEM NO.	QTY. REQD.	DESCRIPTION	PART NO.	WT.	MAT'L	REMARKS
1	1	*ENCLOSURE 16X10X6 NEMA 12	73-0110			A-1610CH (NOT SHOWN)
2	1	PANEL	73-0111			A-16P10 (NOT SHOWN)
3	1	INVERTER	80-0041			MSM1AR
4	1	MAIN LINE CONTACTOR	75-0002			100-C23D10
5	1	TRANSFORMER 100VA	75-0073			TB100A008C
6	3	6 AMP FUSE	74-0064			ATQ6
7	1	FUSE BLOCK	74-0029			BM6033B
8	1	1 1/4 AMP FUSE	74-0018			AGC1 1/4
9	0	FUSE HOLDER	74-0005			NOT USED
10	17	TERMINAL BLOCK	75-0005			6G38-TSKK-F
11	2	TERMINAL END	75-0006			6G38EF
12	1	MOTOR	SEE CHART			460V 3PH 60HZ

*NOTE: ENCLOSURE IS NOT NEMA 4 RATED.

MAIN PANEL, TRACK BOSS- 1MTR MONORAIL, BRIDGE, OR TROLLEY-ONLY DRIVE

REVISION DESCRIPTION:


DRN.: JRG	DATE: 10/3/18	 MORGANTOWN BUSINESS PARK, HEMLOCK ROAD, MORGANTOWN, PA. 19543	
CHKD.: ATG	DATE: 10/3/18		
APPVD.:	DATE:	MAIN PANEL 2 SP.W/INVERTER 460/3/60 MONORAIL, BRIDGE, OR TROLLEY-ONLY, 1/3HP MTR NEMA 12 ONLY	
SCALE: NTS			
PROJECT NO.: ELECT		PLOT DATE:	DWG. NO.
ACAD FILE:		STATUS: FAB	95-460-.3-ETM-1M-ECON
			REV. —

SELECT MOTOR (NON-WASHDOWN)		
MOTOR	PART No.	SET INVERTER / U22
1/3 HP	48-0001	1.3 AMP (.65 EA. MOTOR)

SELECT MOTOR (WASHDOWN)		
MOTOR	PART No.	SET INVERTER / U22
1/3 HP	48-0012SS	1.3 AMP (.65 EA. MOTOR)


BILL OF MATERIALS						
ITEM NO.	QTY. REQD.	DESCRIPTION	PART NO.	WT.	MAT'L.	REMARKS
1	1	*ENCLOSURE 16X10X6 NEMA 12	73-0110			A-1610CH (NOT SHOWN)
2	1	PANEL	73-0111			A-16P10 (NOT SHOWN)
3	1	INVERTER	80-0040			MSM2AR
4	1	MAIN LINE CONTACTOR	75-0002			100-C23D10
5	1	TRANSFORMER 100VA	75-0073			TB100A008C
6	3	6 AMP FUSE	74-0064			ATQ6
7	1	FUSE BLOCK	74-0029			BM6033B
8	1	1 1/4 AMP FUSE	74-0018			AGC1 1/4
9	0	FUSE HOLDER	74-0005			NOT USED
10	17	TERMINAL BLOCK	75-0005			6G38-TSKK-F
11	2	TERMINAL END	75-0006			6G38EF
12	2	MOTOR	SEE CHART			460V 3PH 60HZ

*NOTE: ENCLOSURE IS NOT NEMA 4 RATED.



MAIN PANEL, TRACK BOSS FOR 2 MOTOR BRIDGE, ENCLOSED TRACK

REVISION DESCRIPTION:

DRN.: JRG	DATE: 10/2/18	 MORGANTOWN BUSINESS PARK, HEMLOCK ROAD, MORGANTOWN, PA. 19543			
CHKD.: ATG	DATE: 10/2/18				
APPVD.:	DATE:	MAIN PANEL 2 SP.W/INVERTER 460/3/60 FOR 2MTR BRIDGE, (2) 1/3HP MOTOR NEMA 12 ONLY			
SCALE: NTS					
PROJECT NO.: ELECT		PLOT DATE:	DWG. NO.	REV. —	
ACAD FILE:		STATUS: FAB	95-460-.3-ETM-2M-ECON		


600, 700, AND 900-SERIES ENCLOSED TRACK TRACTOR DRIVE MANUAL

208-230V SELECT MOTOR (NON-WASHDOWN)		
MOTOR	PART No.	SET INVERTER / U22
1/3 HP	48-0001	1.3 AMP


208-230V SELECT MOTOR (WASHDOWN)		
MOTOR	PART No.	SET INVERTER / U22
1/3 HP	48-0012SS	1.3 AMP

BILL OF MATERIALS						
ITEM NO.	QTY. REQD.	DESCRIPTION	PART NO.	WT.	MAT'L.	REMARKS
1	1	*ENCLOSURE 16X10X6 NEMA 12	73-0110			A-1610CH (NOT SHOWN)
2	1	PANEL	73-0111			A-16P10 (NOT SHOWN)
3	1	INVERTER	80-0045			MSM2A23R
4	1	MAIN LINE CONTACTOR	75-0002			100-C23D10
5	1	TRANSFORMER 100VA	75-0073			TB100A008C
6	3	6 AMP FUSE	74-0064			ATQ6
7	1	FUSE BLOCK	74-0029			BM6033B
8	1	1 1/4 AMP FUSE	74-0018			AGC1 1/4
9	0	FUSE HOLDER	74-0005			NOT USED
10	17	TERMINAL BLOCK	75-0005			6G38-TSKK-F
11	2	TERMINAL END	75-0006			6G38EF
12	1	MOTOR	SEE CHART			208/230V 3PH 60HZ

*NOTE: ENCLOSURE IS NOT NEMA 4 RATED.



MAIN PANEL, TRACK BOSS- 1MTR MONORAIL, BRIDGE, OR TROLLEY-ONLY DRIVE


DRN.: JRG	DATE: 7/18/19	 MORGANTOWN BUSINESS PARK, HEMLOCK ROAD, MORGANTOWN, PA. 19543	
CHKD.:	DATE:		
APPVD.:	DATE:	MAIN PANEL 2 SP.W/INVERTER 208-230/3/60	
SCALE: NTS		MONORAIL, BRIDGE, OR TROLLEY-ONLY, 1/3 HP MTR NEMA 12 ONLY	
PROJECT NO.: ELECT	PLOT DATE:	DWG. NO. 95-230-.3-ETM-1M-ECON	REV. —
ACAD FILE:	STATUS: FAB		

208-230V SELECT MOTOR (WASHDOWN)		
MOTOR	PART No.	SET INVERTER / U22
1/3 HP	48-0012SS	1.3 AMP


*NOTE: ENCLOSURE IS NOT NEMA 4 RATED.



TO POWERED HOIST IF PROVIDED

DRN.: JRG	DATE: 7/18/19	 MORGANTOWN BUSINESS PARK, HEMLOCK ROAD, MORGANTOWN, PA. 19543		
CHKD.:	DATE:			
APPVD.:	DATE:	SUB-PANEL 2 SP. W/INVERTER 208-230/3/60 FOR ENCLOSED TRACK 1/3HP MOTOR NEMA 12 ONLY		
SCALE: NTS				
PROJECT NO.: ELECT	PLOT DATE:	DWG. NO.	REV.	
ACAD FILE: 12/31/13	STATUS: FAB	95-230-.3-ETS-1M-ECON	—	

600, 700, AND 900-SERIES ENCLOSED TRACK TRACTOR DRIVE MANUAL




SELECT MOTOR (NON-WASHDOWN)		
MOTOR	PART No.	SET INVERTER / U22
1/3 HP	48-0054	.45 AMP

SELECT MOTOR (WASHDOWN)		
MOTOR	PART No.	SET INVERTER / U22
1/3 HP	48-0054SS	.45 AMP

BILL OF MATERIALS						
ITEM NO.	QTY. REQD.	DESCRIPTION	PART NO.	WT.	MAT'L.	REMARKS
1	1	*ENCLOSURE 16X10X6 NEMA 12	73-0110			A-1610CH (NOT SHOWN)
2	1	PANEL	73-0111			A-16P10 (NOT SHOWN)
3	1	INVERTER	80-0044			MSM1A57R
4	1	MAIN LINE CONTACTOR	75-0002			100-C23D10
5	1	TRANSFORMER 100VA	75-0034			TB81001
6	3	6 AMP FUSE	74-0064			ATQ6
7	1	FUSE BLOCK	74-0029			BM6033B
8	1	1 1/4 AMP FUSE	74-0018			AGC1 1/4
9	0	FUSE HOLDER	74-0005			NOT USED
10	17	TERMINAL BLOCK	75-0005			6G38-TSKK-F
11	2	TERMINAL END	75-0006			6G38EF
12	1	MOTOR	SEE CHART			575V 3PH 60HZ


*NOTE: ENCLOSURE IS NOT NEMA 4 RATED.



MAIN PANEL, TRACK BOSS- 1MTR MONORAIL, BRIDGE, OR TROLLEY-ONLY DRIVE

DRN.: JRG	DATE: 7/18/19	 MORGANTOWN BUSINESS PARK, HEMLOCK ROAD, MORGANTOWN, PA. 19543	
CHKD.:	DATE:		
APPVD.:	DATE:	MAIN PANEL 2 SP.W/INVERTER 575/3/60 MONORAIL, BRIDGE, OR TROLLEY-ONLY, 1/3HP MTR NEMA 12 ONLY	
SCALE: NTS			
PROJECT NO.: ELECT	PLOT DATE:	DWG. NO. 95-575-.3-ETM-1M-ECON	REV. —
ACAD FILE:	STATUS: FAB		

600, 700, AND 900-SERIES ENCLOSED TRACK TRACTOR DRIVE MANUAL




SELECT MOTOR (NON-WASHDOWN)		
MOTOR	PART No.	SET INVERTER / U22
1/3 HP	48-0054	.90 AMP


SELECT MOTOR (WASHDOWN)		
MOTOR	PART No.	SET INVERTER / U22
1/3 HP	48-0054SS	.90 AMP

BILL OF MATERIALS						
ITEM NO.	QTY. REQD.	DESCRIPTION	PART NO.	WT.	MAT'L.	REMARKS
1	1	*ENCLOSURE 16X10X6 NEMA 12	73-0110			A-1610CH (NOT SHOWN)
2	1	PANEL	73-0111			A-16P10 (NOT SHOWN)
3	1	INVERTER	80-0044			MSM1A57R
4	1	MAIN LINE CONTACTOR	75-0002			100-C23D10
5	1	TRANSFORMER 100VA	75-0034			TB81001
6	3	6 AMP FUSE	74-0064			ATQ6
7	1	FUSE BLOCK	74-0029			BM6033B
8	1	1 1/4 AMP FUSE	74-0018			AGC1 1/4
9	0	FUSE HOLDER	74-0005			NOT USED
10	17	TERMINAL BLOCK	75-0005			6G3B-TSKK-F
11	2	TERMINAL END	75-0006			6G38EF
12	2	MOTOR	SEE CHART			575V 3PH 60HZ

*NOTE: ENCLOSURE IS NOT NEMA 4 RATED.




MAIN PANEL, TRACK BOSS FOR 2 MOTOR BRIDGE, ENCLOSED TRACK

DRN.: JRG	DATE: 7/18/19	 MORGANTOWN BUSINESS PARK, HEMLOCK ROAD, MORGANTOWN, PA. 19543			
CHKD.:	DATE:				
APPVD.:	DATE:	MAIN PANEL 2 SP.W/INVERTER 575/3/60 FOR 2MTR BRIDGE, (2) 1/3 HP MOTOR NEMA 12 ONLY			
SCALE: NTS					
PROJECT NO.: ELECT		PLOT DATE:	DWG. NO. 95-575-.3-ETM-2M-ECON	REV. —	
ACAD FILE:		STATUS: FAB			

23 Spanco® Enclosed Track 600-Series Tractor Drive Manual • 1-800-869-2080 • Spanco.com

BILL OF MATERIALS


ITEM NO.	QTY. REQD.	DESCRIPTION	PART NO.	WT.	MAT'L.	REMARKS
1	1	8 BUTTON PENDANT STATION ASSY	79-0024			
1A	1	MOMENTARY START/STOP SP-A	79-0077			
1B	3	TWO SPEED INSERT	79-0009			



B	07/06/15	JJB	11 WAS TL AND 12 WAS TR								
A	10/7/13	NND	PART WAS NAMED 79-0024-H-MET								
DRAWN	CWG	DATE:	10/18/06	PROJECT NO.:		-		PLOT DATE:	11/17/06	DWG. NO. 79-0024-SS-ET	REV. B
CHKD.	-	DATE:	-	ACAD FILE:		-		STATUS:			

BILL OF MATERIALS

ITEM NO.	QTY. REQD.	DESCRIPTION	PART NO.	WT.	MAT'L.	REMARKS
1	1	8 BUTTON PENDANT STATION ASSY	79-0024			
1A	1	MOMENTARY START/STOP SP-A	79-0077			
1B	3	TWO SPEED INSERT	79-0009			



B	7/10/14	JJR	ADDED NOTES							
A	10/7/13	NND	PART WAS NAMED 79-0024-A-MET							
DRAWN	JJB	DATE	02/08/13	PROJECT NO.:	-	PLOT DATE	02/08/13	DWG. NO.	79-0024-A-ET	REV. B
CHKD.	-	DATE	-	ACD FILE	-	STATUS	-			

TROUBLESHOOTING

Most troubleshooting issues are very simple to fix and can be directly traced back to inexact installation or not following the provided instructions. Ensure that instructions A, B, and C below are followed before troubleshooting. **If you have carefully followed the troubleshooting instructions below and are still experiencing issues, please contact your local Spanco dealer.**

- A. READ THE ENTIRE MANUAL CAREFULLY BEFORE INSTALLING, SERVICING, OR TROUBLESHOOTING CRANES. It is critically important that systems are installed exactly per the installation instructions. Before troubleshooting, all technicians should read the installation and operation manual carefully to understand 100 percent of its contents.
- B. Only trained crane service technicians should work on cranes. Your crane dealer will have access to local certified crane technicians and service staff. If you do not have a local dealer, consult your local Yellow Pages or perform an internet search for local certified crane technicians or inspectors. It is critically important the crane be installed by crane technicians EXACTLY as defined in this manual.
- C. For electrical connections, startup, and troubleshooting, only certified electricians are allowed to perform electrical maintenance. All Spanco electrical systems are tested for proper operations and are verified before final shipment; any work performed by non-certified electricians will void the factory warranty.

1. MOTORS DO NOT TURN OR APPEAR TO NOT BE GETTING POWER

- a) Ensure that the main AC contactor coil is pulling in and staying in when the *ON* button is pushed. If the main contactor is not pulling in, the fuse may be blown. In this case, check the fuse.
- b) Ensure that the motor connection leads are secure and receiving power.
- c) Ensure that the inverter doesn't have an error code. If there is an error code, refer to the inverter manual.

2. OVERLOAD TRIPPED

- a) Ensure that the inverter doesn't have an error code. If there is an error code, refer to the inverter manual.
- b) Adjust the *torque* setting to a lower value.
- c) Adjust the acceleration time to a higher value.
- d) Adjust the current value until the desired current is found.

3. WHEELS TURN BUT DRIVE DOES NOT MOVE (See Number 4 below)

4. DRIVE GETS STUCK AT ONE OR MORE POINTS ALONG THE TRACK

- a) Ensure that the spring pressure on the drive wheel is adjusted properly. See page 3 for more information.
- b) Ensure that the runways are properly aligned and level, especially at all track splice locations, per the system installation instructions.
- c) Ensure that the inverter (Variable Frequency Drive [VFD]) is adjusted properly to accelerate the load. Refer to the inverter manual for more information. If more assistance is needed, please contact the inverter manufacturer.

5. SYSTEM LATERAL DEFLECTION OR SWAYING

NOTE: Spanco systems are designed to be fully compliant with and meet or exceed all applicable strength requirements of OSHA, CMAA, ANSI, AISC, and MMA. All steel structures will deflect when acted upon by a force. Vertical deflection should only be measured at 100 percent of the capacity, never at 125 percent capacity.

- a) Ensure that the crane isn't being *plugged*, which is caused by repeatedly pressing a motor control button.
- b) Ensure that the movable components aren't powered directly into the end stops at full speed. Per ANSI B30.17, contact with end stops should be made with caution. If contact with the end stops is unavoidable, then deceleration zones for powered devices can be employed to prevent impact on the end stops.
- c) If sudden accelerating or decelerating causes the deflection or swaying, adjust the inverter for longer accelerations and decelerations per the inverter manual..
- d) If a Freestanding Workstation Bridge Crane support structure exhibits sway that is deemed undesired, brace the support structure to the building. Spanco is not responsible for structures or foundations provided by others.

REDUCER IPTS, INC. BLUE LINE OPERATING INSTRUCTIONS

LUBRICATION

IPTS gear reducers are pre-filled with lubricant unless specified otherwise at the time of purchase. In applications where a breather is preferred by the customer, breather must be installed on the uppermost surface of the gear reducer housing prior to operating.

IPTS recommends the oil fill be checked prior to operating the reducer. The proper level is to the center of the oil level plug or 60% inside the housing. Each IPTS Blue Line reducer is filled with Petrocanada Synduro 460 1/55 for 5° F to 225° F extreme temperatures.

Higher than normal operating temperatures may develop during an initial break-in period of 250 hours of operation. The surface temperature may reach 225° F or higher. For maximum life expectancy do not allow reducer to operate continuously over 225° F after the initial break-in period.

OIL CAPACITY (Fluid Ounces)

#030 = 2 oz.	#110: worm over = 100 oz., worm under = 75 oz.
#040 = 3 oz.	#110: output vertical = 85 oz., input vertical = 100 oz.
#050 = 5 oz.	#130: worm over = 155 oz., worm under = 115 oz.
#063 = 10 oz.	#130: output vertical = 120 oz., input vertical = 155 oz.
#075 = 20 oz.	#150: worm over = 237 oz., worm under = 173 oz.
#090 = 35 oz.	#150: output vertical = 183 oz., input vertical = 211 oz.

GENERAL INSTRUCTIONS

- 1) IPTS gear reducers are rated for 1750 rpm input, 1.0 service factor. Please consult our catalog for selection guidelines.
- 2) Care must be taken to ensure proper alignment of reducer in conjunction with other equipment at the time of installation to prevent damage to reducer components during operation.
- 3) Auxiliary drive components (including sprockets and pulleys) should be mounted as close as possible to the gear reducer housing (without making actual contact) to reduce the effects of overhung loads.
- 4) Auxiliary drive components should not be force fitted to reducer to avoid damage to gears and/or bearings.

WARNINGS

- 1) Overall operational system safety must be considered at all times.
- 2) While ratios over 15:1 are generally self-locking, reducers should not be relied upon to act as brakes.
- 3) For safe operation of any gear drive, all rotating shafts and auxiliary components must be shielded to conform with applicable safety standards.
- 4) Mounting of reducers in overhead position may be hazardous. Use of external guides or supports is strongly recommended for overhead mounting.

For more information, please contact IPTS, Inc. at 800-428-4431.

PRODUCT WARRANTY COVERAGE

Spanco, Inc. warrants its products to be free from defects in material and workmanship as follows:

- Manual Systems and Equipment: Ten Years
- Motorized Systems and Equipment and Paint and Finishes for Non-Aluminum Components: Two Years

Ten-Year Warranty Coverage:

- Defects in equipment material and workmanship of manual systems and equipment
- Only applies to the wearable wheels on workstation bridge crane end trucks and hoist trolleys

Spanco, Inc. warrants its manual workstation bridge crane, jib crane, and gantry crane products to be free from defects in material and workmanship for a period of ten (10) years or 20,000 hours, commencing on the date of shipment to the first retail purchaser. This warranty extends only to parts that are not subject to normal wear and tear from use (nonwearable), with the exception that it does apply to the wearable wheels supplied on manually operated workstation end trucks and hoist trolleys.

Two-Year Warranty Coverage:

- Defects in equipment material and workmanship of motorized systems and equipment
- Paint coatings and finishes for non-aluminum components

Spanco, Inc. warrants motorized equipment to be free from defects in material and workmanship for a period of two (2) years or 4,000 hours, commencing on the date of shipment to the first retail purchaser. Spanco, Inc. warrants its paint and finishes for a period of two (2) years. Warranty claims related to coatings must be accompanied by documentation of the product's application and environmental conditions from time of delivery to time of claim.

WARRANTY TERMS & CONDITIONS

All warranty claims must be approved by Spanco before any work is performed. Spanco's obligation under this warranty is limited to the replacement or repair of Spanco products at the factory or separate location approved by Spanco. **Other than the above mentioned warranty, Spanco will not honor any other warranties—whether expressed, implied, or statutory—and disclaims any warranties of merchantability or fitness for a particular purpose.** Spanco has the right to reject any warranty claim due to harsh and/or inappropriate environmental conditions.

Spanco Is Not Liable for:

- Indirect, incidental, or consequential damages including lost profits, operating costs, loss of production, or travel expenses
- Components or accessories not manufactured by Spanco
- Defective equipment or system failure caused by misuse, negligence, and improper installation or maintenance
- Equipment that has been used in excess of its rated capacity or beyond its service factors
- Rework and modification of any equipment that has been altered without Spanco's written authorization
- Freight charges and damage incurred by freight carriers
- Any loss, injury, or damage to persons or property resulting from failure or defective operation of material or equipment

Reimbursement Disclaimer:

- Written notice of any claimed system defect must be given to Spanco within ninety (90) days of shipment.
- All requests for reimbursement must be accompanied by proper documentation.
- Reimbursement is provided in the form of a credit unless otherwise approved by Spanco management.
- Reimbursement for labor will be provided at a maximum rate of \$75 per hour.
- All reimbursement is subject to approval by Spanco management.

ABOUT SPANCO[®]

Our Commitment

Spanco professionals are dedicated to designing and manufacturing a variety of material handling solutions that meet all applicable CMAA, ANSI, OSHA, and MMA guidelines and standards. Our team of engineers and industry experts combine many years of experience in the material handling industry to manufacture material handling solutions that are backed by the best warranty in the industry.

Spanco production facilities are certified under the ISO 9001:2015 Quality Management System to provide superior quality products. And every welder at Spanco is certified to handle steel (D1.1) and aluminum (D1.2) in accordance with the rigorous requirements and lab testing established by the American Welders Society (AWS).

Spanco professionals welcome challenging projects that require custom crane engineering. Spanco also offers hundreds of pre-engineered lifting solutions, including Workstation Bridge Cranes, Jib Cranes, Gantry Cranes, Monorails, and Tractor Drives.

Our Production:

All of our systems are designed and manufactured in the United States of America. We have production facilities in Las Vegas, Nevada, and at our headquarters in Morgantown, Pennsylvania.



Morgantown, PA | Las Vegas, NV
Toll Free: (800) 869-2080 | Local: (610) 286-7200 | Outside US: 1-610-286-7200 | Fax: (610) 286-0085
Spanco.com | info@Spanco.com

